



THE
**INTERNATIONAL
METAL HOSE**

CATALOG

INTERNATIONAL SEALSKIN™ EXTRA FLEXIBLE LIQUID-TIGHT METALLIC CONDUIT

(NON-UL CONTRACTOR GRADE. TYPE EFLT)

FEATURES:

- Extra flexible for extra easy use
- Corrosion resistant steel core for lasting mechanical protection
- Durable, abrasion resistant PVC jacket won't wrinkle or shrink from cut ends
- Complete protection against most liquids and moisture vapor
- Resists sunlight, heat, oil and chemical degradation
- Smooth interior for easy wire pull-thru
- Easily cut to length on the job
- Accepts standard liquid-tight connectors
- Delivers long-lasting wiring protection where listed products are not required
- Generally applicable temperature range:
-20° C to +50° C (-5° F to +122° F)
- Standard package is shrink-wrapped coils

USES:

International Sealskin™ gives lasting wiring protection on machine tools, portable tools, presses, welders, pumps, blowers, grinders, conveyors, heating equipment and automated lines for forging, plating, molding, blasting, rolling, die casting, processing, extruding, etc.

SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter		Acceptable External Diameter		Bending Radius in Inches	Approx. Weight of 100 Ft.	Approx. Feet Per Standard Pkg.
	Min.	Max.	Min.	Max.			
EFLT-3/8*	0.484	0.504	0.690	0.710	1-1/2	19.5	100
EFLT-1/2*	0.622	0.642	0.820	0.840	2	24.5	100
EFLT-3/4*	0.820	0.840	1.030	1.050	2-3/4	30	100
EFLT-1*	1.041	1.066	1.290	1.315	5	60.5	100
EFLT-1-1/4*	1.380	1.410	1.630	1.660	6	77.5	100
EFLT-1-1/2*	1.575	1.600	1.865	1.900	7	92	50
EFLT-2*	2.020	2.045	2.340	2.375	9	140	50
EFLT-2-1/2	2.480	2.505	2.840	2.875	11	170	50
EFLT-3	3.070	3.100	3.460	3.500	15-1/2	312	25
EFLT-3-1/2	3.500	3.540	3.960	4.000	18	372	25
EFLT-4	4.000	4.040	4.460	4.500	22	424	25

*Also available on reels.



INTERNATIONAL
METAL HOSE COMPANY

**QUALITY MATERIALS • QUALITY MANUFACTURING
QUALITY PERFORMANCE**

520 Goodrich Road – Bellevue, OH 44811-0149 – Phone: 419.483.7690
Fax: 419.483.8225 – Toll Free: 800.458.6855 – www.metalthose.com

INTERNATIONAL FLEXIBLE STEEL CONDUIT (NON-UL. EXPORT GRADE. TYPE IC)

FEATURES:

- Steel construction
- Hot dip galvanized zinc coating won't flake or peel
- Corrosion resistant
- Smooth interior for easy wire pull-thru
- Lightweight for easier handling
- Easy installation to follow contours
- Built-in flexibility for simplified positioning
- Crush resistant
- Standard connectors available from leading manufacturers

USES:

International Flexible Steel Conduit can be used for an electrical raceway where listed products are not required.

SPECIFICATIONS:

Trade Size And Catalog Number	Acceptable Internal Diameter	Acceptable External Diameter	Bending Radius in Inches	Approx. Weight of 100 Ft.	Approx. Feet Per Standard Coil
IC-3/8	0.375	0.610	2	12	100 or 250
IC-1/2	0.625	0.920	3	23.7	100
IC-3/4	0.812	1.105	4	24.5	100
IC-1	1.000	1.380	5	34	50
IC-1-1/4	1.250	1.630	6-1/4	40	50
IC-1-1/2	1.500	1.950	7-1/2	48	25
IC-2	2.000	2.450	10	72	25
IC-2-1/2	2.500	3.060	12-1/2	112	25
IC-3	3.000	3.560	15	140	25
IC-3-1/2	3.500	4.060	17-1/2	156	25
IC-4	4.000	4.560	20	210	25

*Special packaging: 3/16" and 3/8" - Available in 1000 ft., 1500 ft. and 2000 ft. reels.
1/2" and 3/4" - Available in 500 ft. and 1000 ft. reels.
1" through 4" - Available on reels - consult factory.*



INTERNATIONAL
METAL HOSE COMPANY

**QUALITY MATERIALS • QUALITY MANUFACTURING
QUALITY PERFORMANCE**

520 Goodrich Road - Bellevue, OH 44811-0149 - Phone: 419.483.7690
Fax: 419.483.8225 - Toll Free: 800.458.6855 - www.metallhose.com



INTERNATIONAL
METAL HOSE COMPANY

**QUALITY MATERIALS • QUALITY MANUFACTURING
QUALITY PERFORMANCE**

520 Goodrich Road - Bellevue, OH 44811-0149 - Phone: 419.483.7690
Fax: 419.483.8225 - Toll Free: 800.458.6855 - www.metalhose.com